

ShutOut Product Specifications - Folding

PRODUCT SPECIFICATION - ShutOut Sliding Folding			
GENERAL INFORMATION		PRODUCT OPTIONS	
Product Type:	Folding	Type:	Running
Max Panel Height (without midrail / blade split):	1550		Hanging
Max Panel Height (with midrail):	2400	Fitment Options:	Face Fit (Hanging Only)
Min Panel Width:	500 (dependent on weight / load)		Reveal Fit
Max Panel Width:	850 (dependent on weight / load)	Panel Opening - Running (VistaFold Type):	Opening Left Stacking Right
Max Weight Allowed: (per panel)	Combined 2 panel max of 80kg		Opening Right Stacking Left
Weight Distribution:	Running - Bottom / Hanging - Top		Split Opening
Max Adjustable Blade Stack:	14 (without midrail / blade split)	Panel Configuration - Hanging (Bi-Fold Type):	Option of sets of 2, 3, 4 panels which can be combined into the configuration which is needed
Running - (No Comp)			Free moving not hinging off sides
Head Profile (Reveal):	W - 75 / H - 30	Panel Configuration - Running (VistaFold Type):	Unequal : Stacking to one side - 3, 5, 7, 9 (Hinging from one Side)
Sill Profile (Reveal):	W - 75 / H - 45		Equal : Split Opening - 4, 6, 8, 10, 12, 14 (Hinging from both Sides)
Side Sections (Reveal):	W - 75 / H - 30	Aluminium Colour:	Any Industry Norm ANP/ VP Colours
Hanging		Hardware Colour:	Black, Bronze, Matt Charcoal, White, Silver
Head Profile - (Reveal):	W - 50 / H - 70/85	MINIMUM & MAXIMUM PRODUCT OPENING WIDTH	
Head Profile - (Face Fit):	W - 58 / H - 95/110	Running (VistaFold Type)	
Sill Profile - (Reveal):	W - 50 / H - 20	3 - panels =1578mm / Max = 2626mm	4 - panels =2080mm / Max = 3480mm
Sill Profile - (Face Fit):	W - 58 / H - 74/80	5 - Panels =2584mm / Max = 4334mm	6 - Panels =3088mm / Max = 5190mm
Side Sections (Reveal):	W - 55 / H - 49/64	7 - Panels =3592mm / Max = 6054mm	8 - Panels =4100mm / Max = 6900mm
Side Sections (Face Fit):	W - 58 / H - 73/88	9 - Panels =4600mm / Max = 7750mm	10 - Panels =5112mm / Max = 8610mm
Panel Frame Height:	72	12 - Panels =6120mm / Max = 10320mm	14 - Panels =7120mm / Max = 12030mm
Panel Frame Width:	44	Hanging (Bi-Fold Type)	
PRODUCT UNIQUE FEATURES		2 - panels =1004mm / Max = 1704mm	3 - panels =1510mm / Max = 2560mm
Light Penetration:	Uniquely designed which ensures minimal to no external light penetration Superior to any other shutter within the industry	4 - Panels =2010mm / Max = 3410mm	5 - Panels =2515mm / Max = 4266mm
Safety:	Design includes features to ensure a safety barrier	6 - Panels =3014mm / Max = 5115mm	7 - Panels =3518mm / Max = 5790mm
Weather Resistant:	Will act as a barrier from the external elements in normal weather conditions	8 - Panels =4020mm / Max = 6822mm	9 - Panels =4528mm / Max = 7670mm
Product Options	Design allows for all installation design needs	10 - Panels =5028mm / Max = 8520mm	11 - Panels =5534mm / Max = 9380mm
Panel Assembly:	Uniquely designed panel assembly techniques	12 - Panels =6034mm / Max = 10230mm	
Compensation:	Compensating available on sides, top and bottom		
Locks:	Industry standard locking mechanism available		
Moulded Components:	All exposed moulded components are UV and anti-brittle resistant		
Aluminium:	6063 Grade aluminium used		