

ShutOut Product Specifications - Hinged

| PRODUCT SPECIFICATION - ShutOut Hinged | | | |
|---|---|---|---|
| GENERAL INFORMATION | | PRODUCT OPTIONS | |
| Product Type: | Hinged | Type: | Single |
| Max Panel Height (without midrail / blade split): | 1550 | | Double |
| Max Panel Height (with midrail): | 2400 | | Bi-Fold Double |
| Min Panel Width: | 500 (dependent on weight / load) | Fitment Options: | Face Fit |
| Max Panel Width: | 900 (dependent on weight / load) | | Reveal Fit |
| Max Weight Allowed: (per panel) | 45kg | Aluminium Colour | Any Industry Norm ANP/ VP Colours |
| Weight Distribution: | Side Hung | Hardware Colour: | Black, Bronze, Matt Charcoal, White, Silver |
| Max Adjustable Blade Stack: | 14 (without midrail / blade split) | Opening Sides: | Hinging on Left Only |
| Outer frame Height (Reveal Non-Comp): | 14 (incl overlap 44) | | Hinging on Right Only |
| Outer frame Height - (Reveal Comp): | 49 min / 64 max | | Hinging on Both Sides |
| Outer frame Height - (Face Fit Comp): | 73 min / 88 max | Opening Direction: | Open Inwards or Outwards |
| Outer frame Width (Reveal Non-Comp): | 75 | MINIMUM & MAXIMUM PRODUCT OPENING WIDTH | |
| Outer frame Width - (Reveal Comp): | 55 | Single - Reveal Non Comp | Double - Reveal Non Comp |
| Outer frame Width - (Face Fit): | 58 | 538mm - min | 1046mm - min |
| Panel Frame Height: | 72 | 838mm - max | 1646mm - max |
| Panel Frame Width: | 44 | Bi-Fold - Reveal Non Comp | |
| PRODUCT UNIQUE FEATURES | | 1038mm - min | |
| Light Penetration: | Uniquely designed which ensures minimal to no external light penetration | 1638mm - max | |
| | Superior to any other shutter within the industry | Single - Reveal Comp | Double - Reveal Comp |
| Safety: | Design includes features to ensure a safety barrier | 608mm - min | 1116mm - min |
| Weather Resistant: | Will act as a barrier from the external elements in normal weather conditions | 908mm - max | 1816mm - max |
| Product Options | Design allows for all installation design needs | Bi-Fold - Reveal Comp | |
| Panel Assembly: | Uniquely designed panel assembly techniques | 1109mm - min | |
| Compensation: | Compensating available on sides, top and bottom | 1809mm - max | |
| Locks: | Industry standard locking mechanism available | Single - Face Fit | Double - Face Fit |
| | | 528mm - min | 1036mm - min |
| | | 878mm - max | 1736mm - max |
| Moulded Components: | All exposed moulded components are UV and anti-brittle resistant | Bi-Fold - Face Fit | |
| Aluminium: | 6063 Grade aluminium used | 1028mm - min | |
| | | 1728mm - max | |

