

# ShutOut Product Specifications - Sliding

PRODUCT SPECIFICATION - ShutOut Sliding			
GENERAL INFORMATION		PRODUCT OPTIONS	
Product Type:	Sliding	Type:	Running
Max Panel Height (with midrail):	2600		Hanging
Max Panel Width (without Mullion):	1144	Fitment Options:	FaceFit
Min Panel Width:	500 (dependent on weight / load)		Reveal Fit
Max Panel Width:	2280 (dependent on weight / load)	Panel Configuration Option:	Single
Max Weight Allowed: (per panel)	100kg		Double
Weight Distribution:	Running - Bottom / Hanging - Top		Triple
Max Adjustable Blade Stack:	14 (without midrail / blade split)		Quad
Outer frame Height (Reveal Non-Comp):	65	Aluminium Colour	AnyIndustryNormANP/VP Col our s
Outer frame Height - (Reveal Comp):	49 min / 64 max	Hardware Colour:	Black,Bronze,MatCharcoal, White,Silver
Outer frame Height - (Face Fit Comp):	73 min / 88 max	Opening Sides:	Sliding fromLeft toRight
Outer frame Width (Reveal Non-Comp):	58		SlidingfromRightto Left
Outer frame Width - (Reveal Comp):	55	MINIMUM & MAXIMUM PRODUCT OPENING WIDTH	
Outer frame Width - (Face Fit):	58	Face Fit (incl 65mm overlap)	
Panel Frame Height:	72	Single - without Comp	Single with Comp
Panel Frame Width:	44	Min = NoSides - 370mm Min = SidesNo Comp405mm	Min = 445mm Incl Comp
PRODUCT UNIQUE FEATURES		Max = No Sides - 1370mm Max = Sides No Comp 1405mm	Max = 1445mm Incl Comp
Light Penetration:	Uniquely designed which ensures minimal to no external light penetration	Double - without Comp	Double with Comp
	Superior to any other shutter within the industry	Min = NoSides - 870mm Min = Sides No Comp 906mm	Min = 946mm Incl Comp
Safety:	Design includes features to ensure a safety barrier	Max = No Sides - 4430mm Max = Sides No Comp 4466mm	Max = 4506mm Incl Comp
Weather Resistant:	Will act as a barrier from the external elements in normal weather conditions	Reveal Fit	
Product Options	Design allows for all installation design needs	Double Running	Double Hanging
Panel Assembly:	Uniquely designed panel assembly techniques	Min = No Sides - 928mm Min = Sides No Comp 998mm	Min = 1076mm Incl Comp
Compensation:	Compensating available on sides, top Max = No Sides - 4488mm and bottom	Max = Sides No Comp 4558mm	Max = 4636mm Incl Comp
Locks:	Industry standard locking mechanism available	Triple Running	Triple Hanging
		Min = No Sides - 1356mm Min = Sides No Comp 1427mm	Min = 1506mm Incl Comp
		Max = No Sides - 6696mm Max = Sides No Comp 6767mm	Max = 6846mm Incl Comp
Moulded Components:	All exposed moulded components are UV and anti-brittle resistant	Quad Running	Quad Hanging
		Min = No Sides - 1784mm Min = Sides No Comp 1856mm	Min = 1934mm Incl Comp
Aluminium:	6063 Grade aluminium used	Max = No Sides - 8906mm Max = Sides No Comp 8974mm	Max = 9054mm Incl Comp

